

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Structure spray - 400ml  
Product code : TSP 550

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial  
Consumer uses: Private households (= general public = consumers)  
Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
Function or use category : Coatings and paints, thinners, paint removers, Non industrial spraying, Industrial spraying

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Chemical Europe NV  
Baarbeek 2  
2070 Zwijndrecht  
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89  
[info@chemical.eu](mailto:info@chemical.eu)

#### 1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2	H373
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Danger

Hazardous ingredients :

acetone; propan-2-one; propanone; Reaction mass of ethylbenzene and xylene; Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.

# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P260 - Do not breathe spray.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, eye protection, face protection.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a POISON CENTRE or doctor if you feel unwell.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### Scandinavian countries regulation

#### Denmark

MAL code : 5-3

#### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dimethyl ether	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8	25 - 50	Flam. Gas 1, H220 Press. Gas
Reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0	10 - 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	2.5 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	(EC-No.) 920-750-0	2.5 - 10	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1	2.5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
butanone; ethyl methyl ketone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3	2.5 - 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
HYDROGENATED TALLOWALKONIUM CHLORIDE	(CAS-No.) 61789-72-8 (EC-No.) 263-081-3	0.25 - 1	Not classified
1-methoxy-2-propanol; monopropylene glycol methyl ether	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3	0.1 - 1	Flam. Liq. 3, H226 STOT SE 3, H336

# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	(CAS-No.) 64742-95-6 (EC-No.) 265-199-0 (EC Index-No.) 649-356-00-4	0.1 - 0.25	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304
--	---	------------	---

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Assure fresh air breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: No irritant effect.
First-aid measures after eye contact	: Rinse opened eye for several minutes under running water. Then consult doctor.
First-aid measures after ingestion	: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water fog. extinguishing powder. carbon dioxide (CO2). Alcohol resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Protection during firefighting	: Approved respirator.
--------------------------------	------------------------

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable protective clothing. Keep public away.
------------------	--

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Provide adequate ventilation. Do not flush with water.
-----------------	--

#### 6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
-------------------------------	---

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool place. Take action to prevent static discharges. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Storage conditions	: Keep container closed when not in use. Keep container tightly closed. Protect from heat and direct sunlight.
Special rules on packaging	: Store in a closed container. Container should not be closed gas-tight.

# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

<b>acetone; propan-2-one; propanone (67-64-1)</b>		
EU	Local name	Acetone
EU	IOELV TWA (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	500 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Acétone # Aceton
Belgium	Limit value (mg/m <sup>3</sup> )	1210 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	500 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	2420 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
<b>dimethyl ether (115-10-6)</b>		
EU	Local name	Dimethylether
EU	IOELV TWA (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	1000 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Belgium	Local name	Oxyde de diméthyle # Dimethylether
Belgium	Limit value (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
<b>Xylene (mix)</b>		
WEL	Short-term value: Long-term value: Sk; BMGV	441 mg/m <sup>3</sup> , 100 ppm 220 mg/m <sup>3</sup> , 50 ppm
<b>acetone; propan-2-one; propanone (67-64-1)</b>		
WEL	Short-term value Long-term value	3620 mg/m <sup>3</sup> , 1500 ppm 1210 mg/m <sup>3</sup> , 500 ppm
<b>Butanone (78-93-3)</b>		
WEL	Short-term value: Long-term value: Sk, BMGV	899 mg/m <sup>3</sup> , 300 ppm 600 mg/m <sup>3</sup> , 200 ppm
<b>n-butyl acetate (123-86-4)</b>		
WEL	Short-term value Long-term value	966 mg/m <sup>3</sup> , 200 ppm 724 mg/m <sup>3</sup> , 150 ppm
<b>Carbon black (1333-86-4)</b>		
WEL	Short-term value Long-term value	7 mg/m <sup>3</sup> 3.5 mg/m <sup>3</sup>
<b>1-methoxy-2-propanol (107-98-2)</b>		
WEL	Short-term value: Long-term value: Sk	560 mg/m <sup>3</sup> , 150 ppm 375 mg/m <sup>3</sup> , 100 ppm
<b>DNELs</b>		
<b>Xylene (mix)</b>		
Oral	DNEL Long term-systemic	1.6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer)
		180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	289 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	14.8 mg/m <sup>3</sup> (Consumer)
		77 mg/m <sup>3</sup> (Worker)

# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>acetone; propan-2-one; propanone (67-64-1)</b>		
Oral	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
		186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	2,420 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	200 mg/m <sup>3</sup> (Consumer)
		1,210 mg/m <sup>3</sup> (Worker)
<b>Butanone (78-93-3)</b>		
Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
		1,161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m <sup>3</sup> (Consumer)
		600 mg/m <sup>3</sup> (Worker)
<b>Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics</b>		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
		773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m <sup>3</sup> (Consumer)
		2,035 mg/m <sup>3</sup> (Worker)
<b>PNECs</b>		
<b>Xylene (mix)</b>		
PNEC Freshwater	0.327 (Undefined)	
PNEC Marine water	0.327 (Undefined)	
PNEC Freshwater sediment	12.46 (Undefined)	
PNEC Soil	2.31 (Undefined)	
PNEC Sewage Treatment Plant	6.58 (Undefined)	
PNEC Marine water sediment	12.46 (Undefined)	
<b>acetone; propan-2-one; propanone (67-64-1)</b>		
PNEC Marine water	1.06 (Undefined)	
PNEC Freshwater sediment	30.4 (Undefined)	
PNEC Soil	29.5 (Undefined)	
PNEC Marine water sediment	3.04 (Undefined)	
<b>PNECs</b>		
<b>Xylene (mix)</b>		
PNEC Freshwater	0.327 (Undefined)	
PNEC Marine water	0.327 (Undefined)	
PNEC Freshwater sediment	12.46 (Undefined)	
PNEC Soil	2.31 (Undefined)	
PNEC Sewage Treatment Plant	6.58 (Undefined)	
PNEC Marine water sediment	12.46 (Undefined)	
<b>acetone; propan-2-one; propanone (67-64-1)</b>		
PNEC Marine water	1.06 (Undefined)	
PNEC Freshwater sediment	30.4 (Undefined)	
PNEC Soil	29.5 (Undefined)	
PNEC Marine water sediment	3.04 (Undefined)	
<b>Ingredients with biological limit values</b>		
<b>Xylene (mix)</b>		
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid	
<b>Butanone (78-93-3)</b>		
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one	

## 8.2. Exposure controls

### Appropriate engineering controls:

Always wash your hands immediately after handling this product, and once again before leaving the workplace. Do not breathe gas.

### Hand protection:

# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	5 (> 240 minutes), 6 (> 480 minutes)	0.5		EN 374

### Eye protection:

Protective goggles

Type	Use	Characteristics	Standard
			EN 166

### Respiratory protection:

Device	Filter type	Condition	Standard
	Filter AX (brown), Type P2		

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Colour	: Black.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 55.8 - 56.6 °C
Flash point	: -42 °C
Auto-ignition temperature	: > °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 5200 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.84 g/m <sup>3</sup>
Solubility	: Organic solvent:73.8%
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.7 vol %
Upper explosive limit (UEL)	: 18.6 vol %

### 9.2. Other information

VOC content	: 622.1 g/l VOC-CH 73,79%
-------------	---------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

LD/LC50 values relevant for classification:		
<b>Xylene (mix)</b>		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
<b>acetone; propan-2-one; propanone (67-64-1)</b>		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	7,800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)
<b>Butanone (78-93-3)</b>		
Oral	LD50	>2,193 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
		5,000 mg/kg (rbt)
<b>Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics</b>		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,800 mg/kg (rabbit)
Inhalative	LC50/4 h	>23 mg/l (rat)

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Acute aquatic toxicity : Not classified

Aquatic toxicity		
<b>Xylene (mix)</b>		
NOEC	1.3 mg/l (Fish)	
NOEC (7 day)	0.96 mg/l (Daphnia magna)	
NOEC (72h)	0.44 mg/l (algae)	
NOEC (28 d)	16 mg/l (Bacteria)	
LC50/96h	8.9-16.4 mg/l (Pimephales promelas)	
EC50/48h	3.2-9.5 mg/l (Daphnia magna)	
<b>acetone; propan-2-one; propanone (67-64-1)</b>		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	7,800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)

# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Butanone (78-93-3)</b>	
LC50/96h EC50/48h	2,993 mg/l (Pimephales promelas) 308 mg/l (Daphnia magna)
<b>Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics</b>	
NOELR (72h) EL50 (72h) LL50 (96h) NOEC (21 days) LOEC (21 days) EC50/48h	10 mg/l (Pseudokirchneriella subcapitata) 10-30 mg/l (Pseudokirchneriella subcapitata) >13.4 mg/l (Oncorhynchus mykiss (96h)) 0.17 mg/l (Daphnia magna) 0.32 mg/l (Daphnia magna) 3 mg/l (Daphnia magna)

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations




### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Do not dispose of with domestic waste. Do not discharge into drains.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

<b>ADR</b>	<b>IMDG</b>	<b>IATA</b>	<b>ADN</b>
<b>14.1. UN number</b>			
1950	1950	1950	Not applicable
<b>14.2. UN proper shipping name</b>			
AEROSOLS	AEROSOLS	Aerosols, flammable	Not applicable
<b>Transport document description</b>			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	Not applicable
<b>14.3. Transport hazard class(es)</b>			
2.1	2.1	2.1	Not applicable
			Not applicable
<b>14.4. Packing group</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Not applicable
No supplementary information available			

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 11  
Excepted quantities (ADR) : E0



# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Packing instructions (ADR)	: P207
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

### - Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### - Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### - Inland waterway transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content	: 622.1 g/l
VOC-CH	73,79%

#### 15.1.2. National regulations

Class	Share in %
NK	50-<75

#### Germany

Reference to AwSV : Water hazard class (WGK) 2, significant hazard to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

#### Netherlands

Waterbezuwaarlijkheid : 1 - Black list substance

# Structure spray - 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SZW-lijst van kankerverwekkende stoffen	: Quartz
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: 2-methoxypropanol

### Denmark

Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*